SHINE GRILL 6 W

3000 K track light, dark nickel

DK/EU-5772-DN · Shine Track light, GRILL 3000 series, D74*H28, LED, 48V DC, 6W, RA≥90, 3000K, IP20, dark nickel color, aluminum



POWER **6 W**	LUMINOUS FLUX **390 lm**
COLOUR TEMPERATURE **3000 K**	COLOUR RENDERING **CRI ≥ 90**
BEAM ANGLE **36°**	VOLTAGE **48 V**
CONTROL **On/Off**	PROTECTION **IP20**
DIMENSIONS **74 × 28 mm**	FINISH **Dark nickel**
WARRANTY **3 years**	EAN **3831166002082**


CRI ≥ 90
Colours and materials look natural.

DARK NICKEL FINISH
The same finish across tracks, spots, wall lights and even the driver.

48 V LOW VOLTAGE
Safe to touch and easy to reposition.

SHINE GRILL is light with a built-in LED for the SHINE track system. The light body is made of aluminum, which effectively dissipates heat, and has a matte textured surface. Equipped with LEDs of 6W power with a beam angle of 36° and a high color rendering index of CRI>90. Color temperature of 3000K. Simple installation anywhere on the track. Available in satin brass.

OVERALL DIMENSIONS, MM



PART OF DENKIRS SHINE

One finish, one scheme

Satin brass or dark nickel across tracks, spots, wall lights, downlights — and even the driver.

Base or Hide

Base mounts on the surface or on suspensions; Hide recesses flush into 12.5 mm plasterboard.

48 V low voltage

Safe to touch. A 150 W external driver feeds the track, with power inputs for surface and suspended mounting.

TECHNICAL DATA

LIGHT

Power	6 W
Luminous flux	390 lm
Colour temperature	3000 K
Light colour	Warm white
Colour rendering (CRI)	≥ 90
Beam angle	36°
Dimmable	No
Light source	Built-in LED
Base	Built-in LED

POWER & CONTROL

Voltage	48 V
Control	On/Off
Phases	single phase


DIMENSIONS

Width	74 mm
Height	28 mm
Diameter	74 mm


BUILD & ORDER

Finish	Dark nickel
Material	Aluminum
Protection	IP20
Warranty	3 years
Article	DK/EU-5772-DN
EAN barcode	3831166002082
Units per box	50 pcs

LIGHT



Distance · illuminance at the centre · spot diameter at half intensity.
Photometric file, 390 lm.



Light distribution, cd/klm: C0–C180 solid red, C90–C270 dashed.

WORKS WITH

TR/EU-5710-DN Track Shine, Base series, 1 M, 48V DC, IP20, dark nickel color, aluminum

TR/EU-5715-DN Track Shine, Base series, 1.5 M, 48V DC, IP20, dark nickel color, aluminum

TR/EU-5721-DN Power supply, Shine track system, Base series, 48V DC, IP20, dark nickel color, aluminum

TR/EU-5735-DN Low profile end cap, for use without decorative track cover, Shine track system, Base series, set of 2 pieces, dark nickel color, aluminum