Flush mounting track SMART

TR/EU-2012-BK · Flush mounting track SMART



VOLTAGE
220 V

DIMENSIONS
2000 × 70 × 56 mm

FINISH
Black

WARRANTY
3 years

EAN
3831166000378

Track system SMART for recessed installation in drywall. It has special flanges-stops over the entire area, thanks to which it is securely fixed in the material of the suspended ceiling by the flush-mounted method. It is the best solution for recessed installation in drywall. End caps are included. Optional accessories: power supply, connectors and decorative screens are sold separately. The busbar is connected to the mains voltage AC 220V.

OVERALL DIMENSIONS, MM



PART OF DENKIRS SMART

220 V, no driver

The track connects straight to the mains. No driver to size, no transformer to hide.

Four installation types

Surface, suspended, recessed in plasterboard — or SMART ONE for stretch ceilings.

Pairing, not wiring

Remotes, wall panels and the app connect over Bluetooth, Wi-Fi or Zigbee — no control cables to run.

TECHNICAL DATA

POWER & CONTROL

Voltage	220 V

DIMENSIONS

Length	2000 mm
Width	70 mm
Height	56 mm

BUILD & ORDER

Finish	Black
Material	Aluminum
Warranty	3 years
Article	TR/EU-2012-BK
EAN barcode	3831166000378
Units per box	5 pcs