Power feed for suspended mounting of the SMART BASE track, AC 220–240 V, IP20, 5 m, black, aluminum

TR/EU-2124-BK · Power feed for suspended mounting of the SMART BASE track, AC 220-240 V, IP20, 5 m, black, aluminum



VOLTAGE	PROTECTION
220-240V AC	IP20
DIMENSIONS	FINISH
50 × 5000 mm	Black
WARRANTY	EAN
3 years	3831166003935

Power feed for suspended installation of the SMART BASE track. Adjustable length up to 5 m. Essential for the suspended track mounting method.

OVERALL DIMENSIONS, MM



PART OF DENKIRS SMART

220 V, no driver

The track connects straight to the mains. No driver to size, no transformer to hide.

Four installation types

Surface, suspended, recessed in plasterboard — or SMART ONE for stretch ceilings.

Pairing, not wiring

Remotes, wall panels and the app connect over Bluetooth, Wi-Fi or Zigbee — no control cables to run.

TECHNICAL DATA

POWER & CONTROL

Voltage	220-240V AC

DIMENSIONS

Width	50 mm
Height	5000 mm
Diameter	50 mm
Height adjustable	yes

BUILD & ORDER

Finish	Black
Material	Aluminum
Protection	IP20
Warranty	3 years
Article	TR/EU-2124-BK
EAN barcode	3831166003935
Units per box	50 pcs