

(My)SQL Cheat Sheet

Here are the most commonly used SQL commands and the most commonly used options for each. There are many more commands and options than listed here. In other words, the syntaxes as I have listed them are far from complete. See the links at the bottom for more complete syntaxes and more commands.

MySQL Command-Line		
What	How	Example(s)
Running MySQL	<code>mysql -uusername -ppassword</code>	<code>mysql -ucusack2R0 -pegbdf5s</code>
Importing	<code>mysql -uusername -ppassword < filename</code>	<code>mysql -usomeDB -pblah < myNewDB.sql</code>
Dumping (Saving)	<code>mysqldump -uusername -ppassword database [tables] > filename</code>	<code>mysqldump -ume -pblah myDB > My.sql</code> <code>mysqldump -ume -pblah myDB table1 table2 > my.sql</code>

Common MySQL Column Types		
Purpose	Data Type	Example
Integers	<code>int(M)</code>	<code>int(5)</code>
Floating-point (real) numbers	<code>float(M, D)</code>	<code>float(12, 3)</code>
Double-precision floating-point	<code>double(M, D)</code>	<code>double(20, 3)</code>
Dates and times	<code>timestamp(M)</code>	<code>timestamp(8)</code> (for YYYYMMDD) <code>timestamp(12)</code> (for YYYYMMDDHHMMSS)
Fixed-length strings	<code>char(M)</code>	<code>char(10)</code>
Variable-length strings	<code>varchar(M)</code>	<code>varchar(20)</code>
A large amount of text	<code>blob</code>	<code>blob</code>
Values chosen from a list	<code>enum('value1', value2', ...)</code>	<code>enum('apples', 'oranges', 'bananas')</code>

M is maximum to display, and D is precision to the right of the decimal.

MySQL Mathematical Functions		MySQL String Functions	
What	How	What	How
Count rows per group	<code>COUNT(column *)</code>	Compare strings	<code>strcmp(string1, string2)</code>
Average value of group	<code>AVG(column)</code>	Convert to lower case	<code>lower(string)</code>
Minumum value of group	<code>MIN(column)</code>	Convert to upper case	<code>upper(string)</code>
Maximum value of group	<code>MAX(column)</code>	Left-trim whitespace (similar right)	<code>ltrim(string)</code>
Sum values in a group	<code>SUM(column)</code>	Substring of string	<code>substring(string, index1, index2)</code>

Absolute value	abs(number)	Encrypt password	password(string)
Rounding numbers	round(number)	Encode string	encode(string, key)
Largest integer not greater	floor(number)	Decode string	decode(string, key)
Smallest integer not smaller	ceiling(number)	Get date	curdate()
		Get time	curtime()
Square root	sqrt(number)	Extract day name from date string	dayname(string)
nth power	pow(base, exponent)	Extract day number from date string	dayofweek(string)
random number n, 0 < n < 1	rand()	Extract month from date string	monthname(string)
sin (similar cos, etc.)	sin(number)		

Basic MySQL Commands		
What	How	Example(s)
List all databases	SHOW DATABASES;	SHOW DATABASES;
Create database	CREATE DATABASE database;	CREATE DATABASE PhoneDB;
Use a database	USE database;	USE PhoneDB;
List tables in the database	SHOW TABLES;	SHOW TABLES;
Show the structure of a table	DESCRIBE table; SHOW COLUMNS FROM table;	DESCRIBE Animals; SHOW COLUMNS FROM Animals;
Delete a database (Careful!)	DROP DATABASE database;	DROP DATABASE PhoneDB;

SQL Commands: Modifying		
What	How	Example(s)
Create table	CREATE TABLE table (column1 type [[NOT] NULL] [AUTO_INCREMENT], column2 type [[NOT] NULL] [AUTO_INCREMENT], ... other options, PRIMARY KEY (column(s)));	CREATE TABLE Students (LastName varchar(30) NOT NULL, FirstName varchar(30) NOT NULL, StudentID int NOT NULL, Major varchar(20), Dorm varchar(20), PRIMARY KEY (StudentID));
Insert data	INSERT INTO table VALUES (list of values); INSERT INTO table SET column1=value1, column2=value2, ... columnk=valuek; INSERT INTO table (column1, column2, ...) VALUES (value1, value2...);	INSERT INTO Students VALUES ('Smith', 'John', 123456789, 'Math', 'Selleck'); INSERT INTO Students SET FirstName='John', LastName='Smith', StudentID=123456789, Major='Math'; INSERT INTO Students (StudentID, FirstName, LastName) VALUES (123456789, 'John', 'Smith');
Insert/Select	INSERT INTO table (column1, column2, ...) SELECT statement; (See below)	INSERT INTO Students (StudentID, FirstName, LastName) SELECT StudentID, FirstName, LastName FROM OtherStudentTable;

		WHERE LastName like '%son';
Delete data	DELETE FROM table [WHERE condition(s)];	DELETE FROM Students WHERE LastName='Smith'; DELETE FROM Students WHERE LastName like '%Smith'; AND FirstName='John'; DELETE FROM Students;
	(Omit WHERE to delete all data)	
Updating Data	UPDATE table SET column1=value1, column2=value2, ... columnk=valuek [WHERE condition(s)];	UPDATE Students SET LastName='Jones' WHERE StudentID=987654321; UPDATE Students SET LastName='Jones', Major='Theatre' WHERE StudentID=987654321 OR (MAJOR='Art' AND FirstName='Pete');
Insert column	ALTER TABLE table ADD COLUMN column type options;	ALTER TABLE Students ADD COLUMN Hometown varchar(20);
Delete column	ALTER TABLE table DROP COLUMN column;	ALTER TABLE Students DROP COLUMN Dorm;
Delete table (Careful!)	DROP TABLE [IF EXISTS] table;	DROP TABLE Animals;

SQL Commands: Querying		
What	How	Example(s)
All columns	SELECT * FROM table;	SELECT * FROM Students;
Some columns	SELECT column1,column2,... FROM table;	SELECT LastName, FirstName FROM Students;
Some rows/ columns	SELECT column1,column2,... FROM table [WHERE condition(s)];	SELECT LastName,FirstName FROM Students WHERE StudentID LIKE '%123%';
No Repeats	SELECT [DISTINCT] column(s) FROM table;	SELECT DISTINCT LastName FROM Students;
Ordering	SELECT column1,column2,... FROM table [ORDER BY column(s) [DESC]];	SELECT LastName,FirstName FROM Students ORDER BY LastName, FirstName DESC;
Column Aliases	SELECT column1 [AS alias1], column2 [AS alias2], ... FROM table1;	SELECT LastName,FirstName AS First FROM Students;
Grouping	SELECT column1,column2,... FROM table [GROUP BY column(s)];	SELECT LastName,COUNT(*) FROM Students GROUP BY LastName;
Group Filtering	SELECT column1,column2,... FROM table [GROUP BY column(s)] [HAVING condition(s)];	SELECT LastName,COUNT(*) FROM Students GROUP BY LastName HAVING LastName like '%son';
Joins	SELECT column1,column2,... FROM table1,table2,... [WHERE condition(s)];	SELECT LastName,Points FROM Students,Assignments WHERE AssignmentID=12 AND Students.StudentID=Assignments.StudentID;
Table Aliases	SELECT column1,column2,... FROM table1 [alias1], table2 [alias2],... [WHERE condition(s)];	SELECT LastName,Points FROM Students S,Assignments A WHERE S.StudentID=A.StudentID AND A.AssignmentID=12;

Everything	<pre> SELECT [DISTINCT] column1 [AS alias1], column2 [AS alias2], ... FROM table1 [alias1], table2 [alias2],... [WHERE condition(s)] [GROUP BY column(s)] [HAVING condition(s)] [ORDER BY column(s)] [DESC]]; </pre>	<pre> SELECT Points, COUNT(*) AS Cnt FROM Students S,Assignments A WHERE S.StudentID=A.StudentID AND A.AssignmentID=12 GROUP BY Points HAVING Points > 10 ORDER BY Cnt, Points DESC; </pre>
------------	--	--

For more details, see the following pages from [MySQL. com](https://www.mysql.com/).

- [MySQL Reference Manual](#)
- [MySQL Column Types](#)
- [SHOW syntax](#)
- [CREATE TABLE syntax](#)
- [ALTER TABLE syntax](#)
- [INSERT syntax](#)
- [DELETE syntax](#)
- [UPDATE syntax](#)
- [SELECT syntax](#)
- [INSERT ... SELECT syntax](#)
- [MySQL Functions](#)